



OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)



OK-HNVR2208

Model		OK-HNVR2208
OS		Embedded Linux
Video&Audio input	Incoming bandwidth	60Mbps
	IPC Input	8CH
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768
	HDMI	1.4a
		3840×2160,1920×1080,1280×1024,1280×720,1024×768
	Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)
Video&Audio encoding	Audio Compression	G.711A
	Audio Bit Rate	64Kbps
Video&Audio decoding	IP channel Resolution	Main stream:Up to 2560x1920 Auxiliary stream:D1
	Video decoding	H.265 (Main Profile@L5.0 High-tie) / H.264 Up to High Profile@Level5.0)
	Audio decoding	G.711A/G711U/ACC
	Synchronous Playback	8CH
	Decoding Ability	4CH 1080P@30FPS
Intelligent Analysis		1CH Face detection or 1CH Perimeter detection
		Up to 1080P
Other Function	Bidirectional Talk	Two-way voice intercom function
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)
	Picture Capture	Support JPEG Capture
HDD Interface	SATA	1 SATA Interface
	Max Capacity	Unlimited
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
	USB	2*USB2.0
Structure	Dimensions	250*355*55mm
	Size	215*215*50mm
	Weight	0.9KG
	Installation	Desktop Installation
General	Power Supply	DC 12V 2A
	Working Temperature	-10℃--+55℃
	Working Humidity	10%--90%
	Consumption	7W(without HDD)