



OKAMI
CCTV

OKAMI ENTERPRISES CO.,LTD.

HTTPS://OKAMI.CO.TH



OK-HNVR8132

Model	OK-HNVR8132		
OS	Embedded Linux		
Video&Audio input			
Bidirectional Talk	1CH,RCA(Line in,2Vp-p,1Kohms)		
Incoming bandwidth	128Mbps	200Mbps	256Mbps
IPC Input	16CH	32CH	64CH
Video&Audio output			
VGA	1CH,1920×1080,1280×1024,1280×720,1024×768		
HDMI	Standard 2.0		
HDMI	3840×2160, 1920×1080,1280×1024,1280×720,1024×768		
Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)		
Video&Audio encoding			
Audio Compression	G.711A		
Audio Bit Rate	64Kbps		
Video&Audio decoding			
IP channel Resolution	Main stream:Up to 3264x2448,Auxiliary stream:D1		
Video decoding	H.265(Main Profile@L5.0 High-tie)/H.264(Up to High Profile@Level5.0)		
Audio decoding	G.711A/G.726		
Synchronous Playback	Up to 16CH	Up to 32CH	Up to 64CH
Decoding Ability	16CH 1080P@30FPS	16CH 1080P@30FPS	16CH 1080P@30FPS
Intelligent Analysis	1CH Face detection or 2CH Perimeter detection,Up to 1080P		N/A
Other Function			
Bidirectional Talk	Two-way voice intercom function		
Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)		
Picture Capture	Support JPEG Capture		



OKAMI
CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)



OK-HNVR8132

HDD Interface	
SATA	8 SATA Interfaces
eSATA	1 eSATA Interface
Max Capacity	Unlimited
External Interface	
Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet interfaces
USB	3 USB2.0 Interfaces
Alarm Input	16CH, Open/Closed Relay
Alarm Output	4CH,NO/NC
RS-232	1 RS-232 interface
RS-485	1 RS-485 interface
Structure	
Dimensions	520*520*215mm
Size	2U,441*448*88mm
Weight	7Kg(without HDD)
Installation	Rack installation, Desktop installation
General	
Power Supply	110V~220V±10%, 47Hz ~ 63Hz
Working Temperature	0°C-- + 55°C
Working Humidity	10%~90%
Consumption	20W(without HDD)