



OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)

OK-IP620QR-P1

Model		OK-IP620QR-P1
Camera	Image Sensor	1/2.9" SONY Low Illumination CMOS Sensor, HISILICON HI3516C,
	Resolution	2MP
	Effective Pixels	1280(H)×1080(V)
	Compression	H.265/H.264/ JPEG/AVI/MJPEG
	TV System	PAL/NTSC
	Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
	S/N Ratio	≥52dB
	Scanning System	Progressive
	Video Output	Network
	Reset Button	Optional
Lens	Focus Length	3.6mm/F2.0
	Focus Control	Fixed
	Lens Type	Fixed
	Pixels	3MP HD Lens
Night Vision	Infrared LED	6PCS
	Infrared Distance	20M
	IR Status	Under 10 Lux By CDS
	IR Power On	CDS Auto Control
Network	Ethernet	RJ-45 (10/100Base-T)
	Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
	ONVIF	Support ONVIF 2.4
	P2P	YES, Support QR Code
	POE	Optional, Support IEEE 802.3af
	Video Delay	0.3S (Within the Lan)
	Main Stream	1080P@25fps
	Sub Stream	1080P/720P@25fps
	Tri Stream	352*288@25fps
	IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad	



OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)

OK-IP620QR-P1

Camera Features	Day/Night	Color/ B&W (IR-CUT)
	Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
	POE	Support
	Corridor Pattern	Support
	Defog Mode	Support
	ROI	/
	BLC	Support
	HDR	/
	WDR	Support
	Motion Detection	Support
	Privacy Masking	3 Rectangular Zone
	Recording Mode	NVR/NAS/CMS/Web
Interface	Audio	Support
	Alarm	/
	SD Card Slot	Optional
	RS485	Support
General	Housing	Plastic
	Anti-cut Bracket	YES
	IR Cut Filter	YES
	Operation Temperature	-20°C ~ +60°C RH95% Max
	Storage Temperature	-20°C ~ +60°C RH95% Max
	Power Source	DC12V±10%, 850mA
	Dimension	110(W) x 90(H) x 110(D)mm
Weight	380g	