



# OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)



**OK-HNVR2204**

Version		OK-HNVR2204
OS		Embedded Linux
Video&Audio input		Incoming bandwidth
Video&Audio input	IPC Input	48Mbps
Video&Audio output	VGA	4CH
Video&Audio output Video&Audio encoding	HDMI	1CH,1920×1080,1280×1024,1280×720,1024×768
	HDMI	1.4a
	Audio Output	3840×2160,1920×1080,1280×1024,1280×720,1024×768
Audio Compression		1CH,RCA(Line out,2Vp-p,300ohms)
Video&Audio encoding	Audio Bit Rate	G.711A
Video&Audio decoding	IP channel Resolution	64Kbps
Video&Audio decoding Intelligent Analysis	Video decoding	Main stream:Up to 2560x1920 Auxiliary stream:D1
	Audio decoding	H.265 (Main Profile@L5.0 High-tie) / H.264 Up to High Profile@Level5.0)
	Synchronous Playback	G.711A/G711U/ACC
	Decoding Ability	4CH
	1CH Face detection or 1CH Perimeter detection	4CH 1080P@30FPS
Intelligent Analysis		Up to 1080P
Other Function		Bidirectional Talk
Other Function HDD Interface	Motion Detection	Two-way voice intercom function
	Picture Capture	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)
	SATA	Support JPEG Capture
HDD Interface External Interface	Max Capacity	1 SATA Interface
	Network Interface	Unlimited
External Interface Structure	USB	1 RJ45 10M/100M self-adaptive Ethernet interface
	Dimensions	2*USB2.0
Structure General	Size	250*355*55mm
	Weight	215*215*50mm
	Installation	0.9KG
	Power Supply	Desktop Installation
General	Working Temperature	DC 12V 2A
	Working Humidity	-10℃--+55℃
	Consumption	10%--90%