



OKAMI CCTV

OKAMI ENTERPRISES CO.,LTD.

[HTTPS://OKAMI.CO.TH](https://okami.co.th)



OK-IP1820IF-P1

Model		OK-IP1820LF-P1
Camera	Image Sensor	1/2.8" SONY Back-illuminated CMOS Sensor IMX291M+HI3516C
	Resolution	2MP
	Effective Pixels	1945(H)*1097(V)
	Compression	H.264/H.265/JPEG/AVI/MJPEG
	TV System	PAL/NTSC
	Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
	S/N Ratio	≥52dB
	Scanning System	Progressive
	Video Output	Network
	Reset Button	Optional
Lens	Focus Length	3.6mm/F2.0
	Focus Control	Fixed
	Lens Type	Fixed
	Pixels	3MP HD Lens
Night Vision	Infrared LED	14μ x 18PCS
	Infrared Distance	20M
	IR Status	Under 10 Lux By CDS
	IR Power On	CDS Auto Control
Network	Ethernet	RJ-45 (10/100Base-T)
	Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
	ONVIF	Support ONVIF 2.4
	P2P	YES, Support QR Code
	POE	Optional, Support IEEE 802.3af
	Video Delay	0.3S (Within the Lan)
	Main Stream	1080P@12fps, 960P/720P@15fps;
	Sub Stream	1080P/720P@25fps
	Tri Stream	352*288@25fps
	IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad	
Camera Features	Day/Night	Color/ B&W (IR-CUT)
	Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
	POE	Support
	Corridor Pattern	Support
	Defog Mode	Support
	ROI	/
	BLC	Support
	HDR	/
	WDR	Support
	Motion Detection	Support
	Privacy Masking	3 Rectangular Zone
	Recording Mode	NVR/NAS/CMS/Web
Interface	Audio	Optional
	Alarm	/